

Mobile Power





GENERAL TECHNICAL DATA		EHR 90/130
Nominal rated power	kVA	90
Nominal energy storage capacity	kWh	127,8
Rated voltage (50Hz)	VAC	400/230
Maximum power input	A	200*
Maximum passthrough	A	200*
Operating temperature	°C	-15 to 50
Protection		Overload, Overheat, Short Circuit
BATTERIES		
Quantity	Un	36
Type		LFP (LiFePO ₄)
Battery system voltage	VDC	48
DoD % (depth of discharge)		90%
Energy density	Wh/kg	111
Overcurrent capability		up to 2 x recommended current
Lifetime (90% DoD)	Cycles	6000
Battery management system		LFP batteries with built-in BMS
Maintenance charge cycle		1 month
INVERTER		
Quantity	Un.	6
Total nominal power	kVA	90
Max. Charging current	A	1200
OVERLOAD		
Peak power of 200% of the nominal power (short-circuit)		0,5 seconds
150% of nominal power where the output voltage remains stable		5 seconds
130% of nominal power where the output voltage remains stable		30 minutes
Start up current of loads (2 Phase motor)		3 x nominal current

*Passthrough and input current may vary +/-10% depend on conditions and installations.

PERFORMANCE		EHR 90/130
Recommended generator size	kVA	60 - 180
Max outlet hybrid system	A	330
Recharging time / Maintenance time		
Recharging time	h	2,56
Maintenance recharging (@DoD%)	h	16,76
Discharging autonomy		
100% nominal power	h	1,64
75% nominal power	h	2,18
50% nominal power	h	3,28
25% nominal power	h	6,55
RENEWABLE ENERGY		
MPPT		1 x 5kW MPPT
Protections		SPD + MLCB
Max. PV short circuit current		140A (max 30A per MC4 conn.)
Max. PV voltage		250V
Connectors		3 pair 30A - MC4

DIMENSIONS AND WEIGHT		EH 90/130
Dimensions (L x W x H)	mm	2250 x 1200 x 2080
Weight	kg	2695
Batteries Weight	kg	1152



SCOPE OF SUPPLY

CANOPY

- Powder coating with primer coating according to HIMOINSA standards.

ACCESIBILITY

- Wide doors to check servicing and commissioning in customer interface.
- Cables entry

SECURITY

- Internal locker for batteries.
- Antitheft hinges and door lockers.
- Earth pin (grounding rod not included)

TRANSPORTABILITY

- Forklift pockets
- Lifting hook

OPTIONALS

- Custom colors.
- Custom sockets distribution (input and output)
- Automatic Bypass function
- Galvanized baseframe
- Trailer

HIMOINSA has the right to modify any feature without prior notice. The images are indicative and may not coincide in their entirety with the product. Images non contractual.

CONTROL PANEL

Model	HICORE Control module with TFT4.3" display and buttons
Remote generator start	Dry contact relay
Remote communication	3G/4G Dual SIM modem / router. eHR Battery Power Box Software / C2Cloud
Communication	Web APP



HICORE[®] HIMOINSA SYSTEM

HICORE guarantees the optimisation of the different power sources by means of an interface that has been designed to provide a guided and simple experience for any operator, who will be able to choose the most appropriate working mode at any given moment. In addition, to ensure immediate start-up, we offer a Plug&Play mode which allows the EHR to automatically decide which is the best operational option at any given moment based on a constant analysis of the load profile and the connected sources.




Start ASSISTANT to set up a working mode or to charge the batteries.



User experience
Easy system configuration and handling. Smart guidance throughout the start-up process with a wizard, making it easy to operate the unit.



Always connected
Get all the performance info you need through C4CLOUD which comes pre-installed on the unit. Monitor, read and analyse all the performance and load profile information locally or remotely (4G) to optimise your site's power solution.



SOCKETS OPTIONS		400V/50Hz/3p+N
IN	CETAC 5Px125A 400v	-
	CETAC 3Px32A 230v	1
	POWERLOCKS 3ph+n+t	1*
OUT	CETAC 5Px125A 400v	1
	CETAC 5Px63A 400v	1
	CETAC 5Px32A 400v	1
	CETAC/PIM/RIM 3Px16A 230v	2

Every socket include circuit breaker. Power Output protected by Earth Leakage Relay. Domestic sockets with ELR. *The powerlocks option will only be available if the busbar input is not selected.



HIMOINSA has the right to modify any feature without prior notice. The images are indicative and may not coincide in their entirety with the product. Images non contractual.